

New Hampshire

Discover our New Hampshire model. With its vertical lines and well-thought-out spacing between embossing, it offers the possibility to incorporate refined double windows, adding a touch of light and style to your space. Let yourself be charmed by its unique and warm character, which will undoubtedly bring a rustic and authentic ambiance to your home.

Baked paint (2 layers) Primer Galvanization Steel* Galvanization Primer

*For aluminum coating, chromate pretreatment is used instead of galvanization.

Available configurations



Discover your style










Color chart

Dark Oak

Galvanized Steel



Commerical

Slate **Aluminum**





Iron Ore

Black

Technical information

Panel height	18, 21 and 24 inches (45, 53 and 60 cm)
Panel width	1 %": 5 to 18 feet (1,52 m to 5,48 m) 1 %": 4 to 24 feet (1,22 m to 7,32 m)
Door Thickness	1 %" (34,925 mm) / RSI 2,11 (R-12) 1 ¾" (44,45 mm) / RSI 2,81 (R-16)
Windows	1 %": 1542 Standard injected frame (Available inserts)
	1 ¾": 40x13 Standard injected frame
Metal Thickness	26 ga Steel : 0,47 mm (0,0185 in) 23 ga Aluminum : 0,61 mm (0,024 in)
Insulation	High-density polyurethane meeting the highest environmental standards.
End Block	Made of 100% recycled materials - A Garex exclusivity.
Coating	Baked Polyester (2 layers)
Texture	Woodgrain